

Designed for heavy shop or industrial use Ingersoll Rand Two-Stage electric aircompressors provide the quality and performance that are ideal for most applications and users including automotive service and body shops fleet maintenance machine shops production and manufacturing lines construction woodworking shops dry cleaners car washes maintenance/repair shops and farms.

Features

- Durable cast-iron, two-stage design offers extended pump life for years of trouble-free service
- 175 PSI maximum operating pressure.
- 100% continuous duty for tough applications.
- Automatic start/stop control/pressure switch operation.
- Includes motor starter, oil sight glass (10-15 HP only), manual drain and BS5169 tank.



Model Specifications

Model	Motor HP RangeAt Working Pressure	Free Air Delivery m³/hr (cfm)(Horizontal) 7.03 kg/cm²g	Free Air Delivery m³/hr (cfm)(Horizontal) 12.3 kg/cm²g	Air Receiver m³ (lit.)
2340	2 3	15.12 (8.90)	14.58 (8.60)	0.150 (150) 0.225 (225)*
2475	5	24.34 (14.32)	23.78 (13.99)	0.225 (225) 0.300 (300)*
2475	7.5	30.90 (18.20)	30.84 (17.80)	0.225 (225) 0.300 (300)*
2545	7.5 12.5	60.30 (35.50)	59.46 (35.00)	0.300 (300) 0.500 (500)
7100	12.5 20	80.16 (47.20)	79.50 (46.80)	0.300 (300) 0.500 (500)
15T	15 30	133.50 (79.40)	133.02 (78.30)	0.500 (500)

Parts & Accessories

Air Compressor Dryers | Air

Compressor Filters



F-Series Filters



Electronic Drain Valves



Ingersoll Rand (NYSE:IR) advances the quality of life by creating comfortable, sustainable and efficient environments. Our people and our family of brands—including Club Car®, Ingersoll Rand®, Thermo King® and Trane®—work together to enhance the quality and comfort of air in homes and buildings; transport and protect food and perishables; and increase industrial productivity and efficiency. We are a \$14 billion global business committed to a world of sustainable progress and enduring results. For more information, visit www.ingersollrand.com.