



Electrical Driven Single stage and 2 Stage Dry Vacuum Pumps

Producing a vacuum for modern industrial applications requires a method of air removal that is simple, dependable and economical to operate and maintain. All of these requirements are met by the Ingersoll Rand T30 air-cooled reciprocating single-stage and two-stage vacuum pumps.

Features

- These pumps achieve vacuum upto 737mm (29.0" Hg) for single stage and upto 754.4mm (29.7" Hg) for two stage configuration, at sea level.
- These dry type vacuum pumps are ideal for paper handling, food processing, vacuum forming, liquid transfer and many other applications.



Model Specifications

Model	Piston Displacement (cfm)	Vacuum (Hg) inch	Motor (hp)
V235	21.60	29.00	1.5
V235T	10.80	29.60	1.5
V244	34.60	29.00	2.0
V244T	17.30	29.65	2.0
V255	60.00	29.00	5.0
V255T	30.00	29.70	5.0
7V	110.00	29.00	7.5
7VT	55.00	29.65	7.5
15V	149.60	29.20	10.0
15VT	99.00	29.65	10.0

Parts & Accessories

**Air Compressor Dryers | Air
Compressor Filters**



F-Series Filters



Electronic Drain Valves



Ingersoll Rand (NYSE:IR) advances the quality of life by creating comfortable, sustainable and efficient environments. Our people and our family of brands—including Club Car®, Ingersoll Rand®, Thermo King® and Trane®—work together to enhance the quality and comfort of air in homes and buildings; transport and protect food and perishables; and increase industrial productivity and efficiency. We are a \$14 billion global business committed to a world of sustainable progress and enduring results. For more information, visit www.ingersollrand.com.